

View Online at <https://aerobasegroup.com/nsn/4730-00-993-7085>

**Quick Disconnect Method:**

Cam-locking all ends

**Bolt Hole Quantity:**

8

**Basic Shape Style:**

Round first quick disconnect end

**Connection Style:**

Plain first quick disconnect end

**Leg Length:**

5.000 inches second quick disconnect end

**Connection Type:**

Unthreaded internal tube third quick disconnect end

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Flow Angle:**

120.0 degrees

**Outside Diameter:**

6.625 inches

**Thickness:**

0.375 inches

**Bolt Hole Diameter:**

0.437 inches

**Bolt Circle Diameter:**

5.875 inches

**Material Specification:**

Qq-a-601, t5 federal specification single material response

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Style Designator:**

Wye

**Test Data Document:**

81349-mil-c-27487 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

14 type and 1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531y0

**Mil-std (military Standard):**

Mil-a-8625 spec.