

View Online at <https://aerobasegroup.com/nsn/4730-01-006-5099>

**Thread Class:**

2b 1st end

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

**Leg Length:**

1.440 inches 2nd end and 1.500 inches 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Seat Angle:**

12.0 degrees all ends

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.500 inches all ends

**Special Features:**

Supports 1025-01-026-6648; howitzer, med. Towed 155-m, m198

**Material:**

Steel

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment Specification:**

J514 assn standard single treatment response and qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve

**Specification Data:**

96906-ms51852 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

25c figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.