NSN 4730-01-008-3585



View Online at https://aerobasegroup.com/nsn/4730-01- Thread Class: 2b 1st end Maximum Operating Temp: 121.0 degrees fahrenheit 2nd response Connection Style: Swivel nut, flareless (swivel nut attachment method opti Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.625 inches all ends	
2b 1st end Maximum Operating Temp: 121.0 degrees fahrenheit 2nd response Connection Style: Swivel nut, flareless (swivel nut attachment method opti Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	1-008-3585
Maximum Operating Temp: 121.0 degrees fahrenheit 2nd response Connection Style: Swivel nut, flareless (swivel nut attachment method optiling Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
121.0 degrees fahrenheit 2nd response Connection Style: Swivel nut, flareless (swivel nut attachment method opti Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Connection Style: Swivel nut, flareless (swivel nut attachment method optil Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Swivel nut, flareless (swivel nut attachment method optiling Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Leg Length: 2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
2.080 inches 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	otional) (tube) 1st end
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size:	
3000.0 pounds per square inch single response Thread Size:	
Thread Size:	
1 625 inches all ends	
1.020 mones an ends	
Seat Angle:	

12.0 degrees all ends

Flow Angle:

90.0 degrees

Outside Diameter Tube Accommodated:

1.250 inches all ends

Material:

Steel comp 12l14

Material Specification:

66 federal standard single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Un all ends

Furnished Items And Quantity:

2 tube coupling nut w/sleeve

Specification Data:

96906-ms51852 government standard

Shelf Life:

N/a

Unit Of Measure:

NSN 4730-01-008-3585

Tube Elbow - Page 2 of 2



Demilitarization:

No

Fiig:

A080b0