

View Online at <https://aerobasegroup.com/nsn/4730-01-013-2530>

Thread Class:

3a 2nd end

Maximum Operating Temp:

135.0 degrees fahrenheit single response

Connection Style:

Swaged w/ grooves (tube) 1st end

Connection Type:

Unthreaded internal tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Nominallength:

1.530 inches

Special Features:

The internal surface of the permaswage end will be polytetrafloroetnylene coated, per deutsch co, spec no. Dmcp1009, to 0.410 in. Min. 0.435 in. Max, into the fitting bore

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

Media For Which Designed:

Hydraulic fluid 1st response

Surface Treatment:

Plastic inside

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 1st treatment response outside and deutsch co specification no.Dmcp1009 mfr ref 2nd treatment response outside

Style Designator:

Swaged and threaded external

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.