Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-014-1813

Thread Class:	
2a 1st end	
Maximum Operating Temp:	
100.0 degrees fahrenheit single response	
Connection Style:	
Plain (pipe) 2nd end	
Connection Type:	
Fhreaded internal pipe 2nd end	
Naximum Operating Pressure:	
3000.0 pounds per square inch single response	
Fhread Size:	
).875 inches 1st end	
Seat Angle:	
2.0 degrees 1st end	
Dutside Diameter Tube Accommodated:	
).625 inches 1st end	
Nominallength:	
.760 inches	
Naterial:	
Steel comp 12I14 or steel comp 1010	
Naterial Specification:	
6 federal standard single material response	
ledia For Which Designed:	
Hydraulic fluid 1st response	
Surface Treatment Specification:	
514 assn standard single treatment response and qq-p-416	, type 2, cl 3 federal specification single treatment response
Thread Series Designator:	
Jnf 1st end	
Furnished Items And Quantity:	
tube coupling nut w/sleeve	
Specification Data:	
06906-ms51816 government standard and 81343-j514 profes	sional/industrial association standard
Specification Or Standard:	
9d figure	
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
-iig:	
A080b0	

Mil-std (military Standard):

Mil-f-18866 spec.

