

View Online at <https://aerobasegroup.com/nsn/4730-01-026-8702>

Body Style:

Relieved

Concentric Hole Depth:

0.965 inches

Concentric Hole Diameter:

0.135 inches

Overall Length:

1.105 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

1.000 inches

First End Thread Length:

0.403 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.750 inches

Second Diameter From Wrenching Feature:

Between 0.570 inches and 0.600 inches

Third Diameter From Wrenching Feature:

Between 0.740 inches and 0.750 inches

Fourth Diameter From Wrenching Feature:

Between 0.657 inches and 0.662 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.440 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 0.360 inches and 0.380 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

Between 0.435 inches and 0.445 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

Between 0.539 inches and 0.544 inches

First Radial Fluid Hole Diameter:

Between 0.130 inches and 0.140 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.695 inches and 0.715 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 0.930 inches and 0.950 inches

Wrenching Feature Height:

Between 0.150 inches and 0.180 inches

First End Thread Series Designator:

Unf

First End Thread Size:

0.750 inches

Special Features:

Two 0.065 in.Dia holes in hex head for lockwire

Material:

Stainless steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0