

View Online at <https://aerobasegroup.com/nsn/4730-01-026-8720>

Furnished Items:

Screw and lock washer and packing preformed

Recess Diameter:

2.031 inches

Recess Depth:

0.295 inches

Thickness:

0.560 inches

Center To Center Distance Between Bolt Holes Along Width:

1.200 inches

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.830 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.424 inches

Bolt Hole Quantity:

4

Flange Length:

3.160 inches

Flange Width:

2.860 inches

Bolt Hole Diameter:

0.469 inches

Neck Height:

0.320 inches

Flange Section Style:

Recessed face, raised neck

Face Seating Surface Condition:

Ground

Maximum Operating Pressure And Media For Which Designed:

4000.0 pounds per square inch fuel/oil, hydrocarbon

Maximum Operating Temperature And Media For Which Designed:

212.0 degrees fahrenheit fuel/oil, hydrocarbon

Special Features:

Flange is split through the center along the length

Material:

Iron or steel

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, cl 2 federal specification single treatment response

Style Designator:

Rectangular, with bolt holes

Specification Data:

81349-mil-f-52525c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23300