

View Online at <https://aerobasegroup.com/nsn/4730-01-026-8720>

**Furnished Items:**

Screw and lock washer and packing preformed

**Recess Diameter:**

2.031 inches

**Recess Depth:**

0.295 inches

**Thickness:**

0.560 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.200 inches

**Center To Center Distance Between Bolt Holes Along Length:**

2.312 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.830 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.424 inches

**Bolt Hole Quantity:**

4

**Flange Length:**

3.160 inches

**Flange Width:**

2.860 inches

**Bolt Hole Diameter:**

0.469 inches

**Neck Height:**

0.320 inches

**Flange Section Style:**

Recessed face, raised neck

**Face Seating Surface Condition:**

Ground

**Maximum Operating Pressure And Media For Which Designed:**

4000.0 pounds per square inch fuel/oil, hydrocarbon

**Maximum Operating Temperature And Media For Which Designed:**

212.0 degrees fahrenheit fuel/oil, hydrocarbon

**Special Features:**

Flange is split through the center along the length

**Material:**

Iron or steel

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Qq-z-325, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Rectangular, with bolt holes

**Specification Data:**

81349-mil-f-52525c government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23300