## NSN 4730-01-027-8261

Tube To Boss Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-027-8261 **Thread Class:** 2a all ends **Maximum Operating Temp:** 121.0 degrees fahrenheit single response **End Application:** 2320-01-442-1940, truck, cbt, (command bridge transporter) **Connection Style:** Flared (tube) 1st end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.062 inches 2nd end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.625 inches 1st end Nominallength: 1.859 inches Material: Steel Media For Which Designed: Hydraulic fluid single response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232, type m, class 1 military specification single treatment response **Thread Series Designator:** Unf 1st end **Furnished Items And Quantity:** 1 preformed packing **Specification Data:** 81343-j514 professional/industrial association standard **Specification Or Standard:** 3b figure Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 4730-01-027-8261

Tube To Boss Straight Adapter - Page 2 of 2



em			

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-p-16232 spec.