

View Online at <https://aerobasegroup.com/nsn/4730-01-027-8261>

Thread Class:

2a all ends

Maximum Operating Temp:

121.0 degrees fahrenheit single response

End Application:

2320-01-442-1940, truck, cbt, (command bridge transporter)

Connection Style:

Flared (tube) 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Nominallength:

1.859 inches

Material:

Steel

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232, type m, class 1 military specification single treatment response

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 preformed packing

Specification Data:

81343-j514 professional/industrial association standard

Specification Or Standard:

3b figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-p-16232 spec.