

View Online at <https://aerobasegroup.com/nsn/4730-01-032-7432>

Body Style:

Plain

Concentric Hole Depth:

Between 1.657 inches and 1.717 inches

Concentric Hole Diameter:

Between 0.599 inches and 0.619 inches

Overall Length:

Between 2.552 inches and 2.572 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Inverted flare

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

Between 1.359 inches and 1.391 inches

First End Thread Length:

0.438 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 1.059 inches and 1.061 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 1.682 inches and 1.692 inches

First Radial Fluid Hole Diameter:

Between 0.428 inches and 0.448 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 1.391 inches and 1.421 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 2.240 inches and 2.260 inches

Wrenching Feature Height:

Between 0.302 inches and 0.322 inches

First End Thread Qty Per Inch (tpi):

12

First End Thread Series Designator:

Un

First End Seat Angle:

45.0 degrees

First End Thread Size:

1.062 inches

Material:

Aluminum alloy 2014 or aluminum alloy 2024

Material Specification:

Qq-a-266, t6 or t651 federal specification 1st material response or qq-a-261, t6 or t6511 federal specification 1st material response or qq-a-367, t4 federal specification 1st material response or qq-a-267, t4 or t3511 federal specification 2nd material response or qq-a-268, t4 or t351 federal specification 2nd material response or qq-a-355, t4 or t351 federal specification 2nd material response

Surface Treatment:

Anodize

Specification Data:

81343-as4875 professional/industrial association standard and 80205-nas551 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-f-5509 spec.