## NSN 4730-01-046-4671

Swivel Flange To Hose Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-046-4671

Bolt Hole Q	uantity:
-------------	----------

4 1st end

## **Maximum Operating Temp:**

275.0 degrees fahrenheit single response

## **Connection Style:**

Gripping nipple (nose) 2nd end

#### Leg Length:

2.260 inches 1st end

#### Width:

1.464 inches 1st end

#### Length:

1.464 inches 1st end

#### Flange Shape:

Rectangular with holes 1st end

#### **Connection Type:**

Threaded external hose gripping 2nd end

## **Maximum Operating Pressure:**

1500.0 pounds per square inch single response

## Flow Angle:

90.0 degrees

## Thickness:

0.234 inches 1st end

## **Bolt Hole Diameter:**

0.205 inches 1st end

## Center To Center Distance Between Bolt Holes Along Length:

1.038 inches 1st end

## Center To Center Distance Between Bolt Holes Along Width:

1.038 inches 1st end

#### Flange Face Design:

Plain swivel 1st end

## Inside Diameter Hose Accommodated:

0.500 inches 2nd end

## **Outside Diameter Hose Accommodated:**

0.656 inches 2nd end

#### Material:

Steel comp 630 socket

## **Material Specification:**

Qq-s-763 federal specification 4th material response sleeve

## Media For Which Designed:

Hydraulic fluid single response

#### **Surface Treatment:**

Passivate socket

# NSN 4730-01-046-4671

Swivel Flange To Hose Elbow - Page 2 of 2



## **Surface Treatment Specification:**

Mil-f-27272 military specification 5th treatment response socket

## **Furnished Items And Quantity:**

1 hose coupling nut and 1 hose coupling sleeve

## **Specification Data:**

96906-ms27058 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.