NSN 4730-01-047-5991

Tube Elbow - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-01-047-5991 |
|---|
| Thread Class: |
| 3b 1st end |
| Maximum Operating Temp: |
| 275.0 degrees fahrenheit 2nd response |
| Connection Style: |
| Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end |
| Leg Length: |
| 1.560 inches 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 12.0 degrees 2nd end |
| Flow Angle: |
| 90.0 degrees |
| Outside Diameter Tube Accommodated: |
| 0.750 inches 2nd end |
| Material: |
| Steel comp 4130 or steel comp 1137 or steel comp 1141 |
| Material Specification: |
| Mil-s-6758 military specification 1st material response or qq-s-637 federal specification 2nd material response or qq-s-637 federal |
| specification 3rd material response |
| Media For Which Designed: |
| Aeronautical fluid single response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unj 2nd end |
| Specification Data: |
| 80205-nas1762 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 4730-01-047-5991

Tube Elbow - Page 2 of 2



Fiig:

A080b0

Mil-std (military Standard):

Mil-s-6758 spec.