

View Online at <https://aerobasegroup.com/nsn/4730-01-048-3484>

Thread Class:

3b 1st end

Maximum Operating Temp:

275.0 degrees fahrenheit 2nd response

Connection Style:

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

Leg Length:

0.971 inches 3rd end

Connection Type:

Threaded internal tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Seat Angle:

12.0 degrees 3rd end

Outside Diameter Tube Accommodated:

0.500 inches 2nd end

Material:

Steel comp 4130 or steel comp 1137 or steel comp 1141

Material Specification:

Mil-s-6758 military specification 1st material response or qq-s-637 federal specification 2nd material response or qq-s-637 federal specification 3rd material response

Media For Which Designed:

Aeronautical fluid single response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf 1st end

Specification Data:

80205-nas1763 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-s-6758 spec.