NSN 4730-01-048-3489 Tube Tee - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-01-048-3489 |
|--|
| Thread Class: |
| 3b 1st end |
| Maximum Operating Temp: |
| 275.0 degrees fahrenheit 2nd response |
| Connection Style: |
| Swivel nut flareless (swivel nut attachment method optional)(tube) 1st end |
| Leg Length: |
| 1.380 inches 3rd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.875 inches 3rd end |
| Seat Angle: |
| 12.0 degrees 3rd end |
| Flow Angle: |
| 90.0 degrees |
| Seat Radius: |
| 0.400 inches 1st end |
| Outside Diameter Tube Accommodated: |
| 0.625 inches 3rd end |
| Material: |
| Steel comp 4130 or steel comp 1137 or steel comp 1141 |
| Material Specification: |
| B6, aisi/sae 4130 federal standard 1st material response or 66, aisi/sae 1137 federal standard 2nd material response or 66, aisi/sae 114 |
| federal standard 3rd material response |
| Media For Which Designed: |
| Hydraulic fluid 1st response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf all ends |
| Specification Data: |
| 80205-nas1763 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

No

Demilitarization:

NSN 4730-01-048-3489

Tube Tee - Page 2 of 2



Fiig:

A080b0