

View Online at <https://aerobasegroup.com/nsn/4730-01-048-3491>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

275.0 degrees fahrenheit 2nd response

**Connection Style:**

Swivel nut flareless (swivel nut attachment method optional)(tube) 1st end

**Leg Length:**

1.560 inches 3rd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 3rd end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.062 inches 3rd end

**Seat Angle:**

12.0 degrees 3rd end

**Flow Angle:**

90.0 degrees

**Seat Radius:**

0.400 inches 1st end

**Outside Diameter Tube Accommodated:**

0.750 inches 3rd end

**Material:**

Steel comp 4130 or steel comp 1137 or steel comp 1141

**Material Specification:**

Mil-s-6758 military specification 1st material response or qq-s-637 federal specification 2nd material response or qq-s-637 federal specification 3rd material response

**Media For Which Designed:**

Aeronautical fluid single response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf 2nd end

**Specification Data:**

80205-nas1763 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-s-6758 spec.