

View Online at <https://aerobasegroup.com/nsn/4730-01-057-1722>

Body Style:

Plain

Concentric Hole Depth:

1.150 inches

Concentric Hole Diameter:

0.172 inches

Overall Length:

Between 1.834 inches and 1.854 inches

First End Connection Type:

Threaded external tube

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Cotter Pin Hole Diameter:

0.060 inches

Width Across Flats:

0.680 inches

First End Thread Length:

Between 0.469 inches and 0.494 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

Between 1.726 inches and 1.746 inches

First Diameter From Wrenching Feature:

Between 0.430 inches and 0.432 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 1.247 inches and 1.252 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 1.641 inches and 1.661 inches

First Radial Fluid Hole Diameter:

0.172 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 1.021 inches and 1.041 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.646 inches and 1.666 inches

Wrenching Feature Height:

Between 0.168 inches and 0.208 inches

First End Thready Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unf

First End Thread Size:

0.4375 inches

Material:

Stainless steel

Material Specification:

Ams5659 15-5ph assn standard single material response

Surface Treatment:

Passivate or cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0