

View Online at <https://aerobasegroup.com/nsn/4730-01-061-6339>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 3rd end

Leg Length:

0.950 inches 3rd end

Connection Type:

Threaded external tube 3rd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Seat Angle:

37.0 degrees 3rd end

Outside Diameter Tube Accommodated:

0.312 inches 3rd end

Material:

Steel comp 12L14

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 2nd treatment response

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

1 bulkhead nut and 2 tube coupling nut w/sleeve and 1 flat washer

Specification Data:

81349-mil-f-18866 government specification and 96906-ms51530 government standard

Specification Or Standard:

1 class and 4 type and 8 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.