

View Online at <https://aerobasegroup.com/nsn/4730-01-062-2570>

Thread Pitch Diameters:

+0.4991/+0.5030 inches 1st end

Maximum Operating Temp:

200.0 degrees fahrenheit single response

End Application:

Multi app; truck, fire/crash p19, p15, p22; tractor, aircraft towing, mb-4, a/s32u30; tractor, flightline towing; truck, refueling a/s32r-11; trailer, semi, m870, m872a1, m872a2, m872a3; 2330-01-275-7474 hemat trailer, 4210-01-486-1035, tfft (tactical fire fighting truck); family of hemtt vehicles (heavy expanded mobility tactical trucks)

Connection Style:

Plain (pipe) 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

0.531 inches 1st end

Seat Angle:

37.0 degrees 1st end

Seat Radius:

0.625 inches 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Nominallength:

1.210 inches

Material:

Copper alloy

Media For Which Designed:

Air single response

Thread Series Designator:

Uns 1st end

Furnished Items And Quantity:

1 tube coupling nut w/sleeve

Specification Data:

81343-j246 professional/industrial association standard

Specification Or Standard:

6a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0