# NSN 4730-01-062-2570

Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-062-2570

Thread Pi	tch Diar	neters:
-----------	----------	---------

+0.4991/+0.5030 inches 1st end

### **Maximum Operating Temp:**

200.0 degrees fahrenheit single response

### **End Application:**

Multi app; truck, fire/crash p19, p15, p22; tractor, aircraft towing, mb-4, a/s32u30; tractor, flightline towing; truck, refueling a/s32r-11; trailer, semi, m870, m872a1, m872a2, m872a3; 2330-01-275-7474 hemat trailer, 4210-01-486-1035, tfft (tactical fire fighting truck); family of hemtt vehicles (heavy expanded mobility tactical trucks)

### **Connection Style:**

Plain (pipe) 2nd end

### **Connection Type:**

Threaded external tube 1st end

### Thready Qty Per Inch (tpi):

24 1st end

### **Maximum Operating Pressure:**

150.0 pounds per square inch single response

#### **Thread Size:**

0.531 inches 1st end

### Seat Angle:

37.0 degrees 1st end

# Seat Radius:

0.625 inches 1st end

### **Outside Diameter Tube Accommodated:**

0.375 inches 1st end

# Nominallength:

1.210 inches

# Material:

Copper alloy

#### Media For Which Designed:

Air single response

# **Thread Series Designator:**

Uns 1st end

### **Furnished Items And Quantity:**

1 tube coupling nut w/sleeve

### **Specification Data:**

81343-j246 professional/industrial association standard

# **Specification Or Standard:**

6a figure

# Shelf Life:

N/a

# **Unit Of Measure:**

--

### **Demilitarization:**

No

# NSN 4730-01-062-2570

Pipe To Tube Straight Adapter - Page 2 of 2



Fiig:

A080b0