

View Online at <https://aerobasegroup.com/nsn/4730-01-064-2514>

**Thread Class:**

3a external

**Thread Direction:**

Right-hand external

**Head Height:**

0.320 inches

**Overall Length:**

1.062 inches

**Maximum Operating Temp:**

275.0 degrees fahrenheit

**Connection Style:**

Flareless

**Thready Qty Per Inch (tpi):**

12 external

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

1.312 inches external

**Seat Angle:**

12.0 degrees

**Material:**

Steel comp 304 or steel comp 316

**Material Specification:**

66, aisi 304/sae 30304 federal standard 1st material response or 66, aisi 316/sae 30316 federal standard 2nd material response

**Media For Which Designed:**

Hydraulic fluid and water, fresh

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification 1st treatment response and qq-p-35, type 1 federal specification 2nd treatment response

**Style Designator:**

Plug, tube fitting flareless (note: drilled hole is optional should not be considered as a separating characteristic)

**Thread Series Designator:**

Unj external

**Specification Data:**

96906-ms21913 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A208a0

**Mil-std (military Standard):**

Mil-s-5002 spec.