

View Online at <https://aerobasegroup.com/nsn/4730-01-064-2514>

Thread Class:

3a external

Thread Direction:

Right-hand external

Head Height:

0.320 inches

Overall Length:

1.062 inches

Maximum Operating Temp:

275.0 degrees fahrenheit

Connection Style:

Flareless

Thready Qty Per Inch (tpi):

12 external

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.312 inches external

Seat Angle:

12.0 degrees

Material:

Steel comp 304 or steel comp 316

Material Specification:

66, aisi 304/sae 30304 federal standard 1st material response or 66, aisi 316/sae 30316 federal standard 2nd material response

Media For Which Designed:

Hydraulic fluid and water, fresh

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification 1st treatment response and qq-p-35, type 1 federal specification 2nd treatment response

Style Designator:

Plug, tube fitting flareless (note: drilled hole is optional should not be considered as a separating characteristic)

Thread Series Designator:

Unj external

Specification Data:

96906-ms21913 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A208a0

Mil-std (military Standard):

Mil-s-5002 spec.