NSN 4730-01-066-1278

Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-066-1278 **Thread Class:** 2a 1st end **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **End Application:** Fkf ground power generator system (gpgs); 2320-01-304-2277 pls (palletized loading system); 1-1/4 ton hmmwv **Connection Style:** Plain (pipe) 2nd end **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Criticality Code Justification:** Feat **Outside Diameter Tube Accommodated:** 0.625 inches 1st end Nominallength: 1.700 inches **Special Features:** Weapon system essential Material: Steel Media For Which Designed:

Hydraulic fluid single response

Surface Treatment Specification:

J514 assn standard single treatment response

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 tube coupling nut w/sleeve

Specification Data:

96906-ms51500 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

2a figure

Shelf Life:

N/a

Unit Of Measure:

NSN 4730-01-066-1278

Pipe To Tube Straight Adapter - Page 2 of 2



Demi			

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.