

View Online at <https://aerobasegroup.com/nsn/4730-01-070-9214>

Thread Class:

2a external

Thread Direction:

Right-hand external

Head Height:

0.250 inches

Overall Length:

0.940 inches

End Application:

Assault amphibious vehicle, command (aavc-7a1); armored cmbat earthmover (m9); truck, forklift, 6000 lb, e60xl; truck, cargo, dropside 2 1/2-ton 6x6 w/e; truck, forklift, 4000 lb, e40xl; scraper tractor, wheeled; interior bay bridge, floating, nsn 5420-00-071-5322; scraper (621b); sealift support facilities program (ssfp) equipment; truck, heavy expanded mobility tactical (hemtt)

Connection Style:

Flared

Thread Size:

0.750 inches external

Seat Angle:

37.0 degrees

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Steel

Surface Treatment:

Zinc and chromate

Style Designator:

Plug, tube fitting flared (note: drilled hole is optional should not be considered as a separating characteristic

Thread Series Designator:

Unf external

Specification Data:

96906-ms51518 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

3d figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A208a0

Mil-std (military Standard):

Mil-f-18866 spec.