

View Online at <https://aerobasegroup.com/nsn/4730-01-075-1945>

Furnished Items:

Screw and lock washer and packing preformed

Recess Diameter:

2.844 inches

Recess Depth:

0.355 inches

Thickness:

0.620 inches

Pipe Size For Which Designed:

2.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.700 inches

Center To Center Distance Between Bolt Holes Along Length:

3.062 inches

Outside Edge To Bolt Hole Center Distance Along Width:

1.050 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.469 inches

Bolt Hole Quantity:

4

Flange Length:

Between 3.940 inches and 4.060 inches

Flange Width:

3.800 inches

Bolt Hole Diameter:

0.531 inches

Neck Height:

0.410 inches

Flange Section Style:

Recessed face, raised neck

Face Seating Surface Condition:

Ground

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch fuel/oil, hydrocarbon

Maximum Operating Temperature And Media For Which Designed:

212.0 degrees fahrenheit fuel/oil, hydrocarbon

Special Features:

Flange is split through the center along the length

Material:

Iron or steel

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, class 2 federal specification single treatment response

Style Designator:

Rectangular, with bolt holes

Specification Data:

81349-mil-h-52525c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300