

View Online at <https://aerobasegroup.com/nsn/4730-01-076-3738>

Recess Diameter:

Between 1.209 inches and 1.229 inches

Recess Depth:

Between 0.240 inches and 0.250 inches

Thickness:

0.500 inches

Tube Outside Diameter For Which Designed:

0.500 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.678 inches and 0.698 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.490 inches and 1.510 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.550 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.330 inches

Bolt Hole Quantity:

4

Flange Length:

2.160 inches

Flange Width:

1.800 inches

Bolt Hole Diameter:

Between 0.334 inches and 0.354 inches

Neck Height:

0.250 inches

Flange Section Style:

Recessed face, raised neck

Face Seating Surface Condition:

Ground

Maximum Operating Pressure And Media For Which Designed:

5000.0 pounds per square inch fuel/oil, hydrocarbon

Maximum Operating Temperature And Media For Which Designed:

212.0 degrees fahrenheit fuel/oil, hydrocarbon

Special Features:

Split flange type

Material:

Iron or steel

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, class 2 federal specification single treatment response

Style Designator:

Rectangular, with bolt holes

Specification Data:

81349-mil-f-52525c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23300