

View Online at <https://aerobasegroup.com/nsn/4730-01-077-7995>

**Thread Class:**

3a external

**Thread Direction:**

Right-hand external

**Head Height:**

0.194 inches

**Overall Length:**

0.734 inches

**Connection Style:**

Flared

**Features Provided:**

Safety wire hole

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.438 inches external

**Seat Angle:**

37.0 degrees

**Material:**

Aluminum alloy 2014 or aluminum alloy 2024 or aluminum alloy 7075

**Material Specification:**

Qq-a-225/4, temper t6 federal specification 1st material response or qq-a-225/6, temper t6 federal specification 2nd material response or qq-a-225/6, temper t851 federal specification 2nd material response or qq-a-225/9, temper t73 federal specification 3rd material response

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 2 military specification single treatment response

**Style Designator:**

Plug, tube fitting flared (note: drilled hole is optional should not be considered as a separating characteristic)

**Thread Series Designator:**

Unjf external

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A208a0

**Mil-std (military Standard):**

Mil-a-8625 spec.