

View Online at <https://aerobasegroup.com/nsn/4730-01-083-4432>

Furnished Items:

Screw and lock washer and packing, preformed

Recess Diameter:

1.531 inches

Recess Depth:

0.245 inches

Thickness:

0.562 inches

Pipe Size For Which Designed:

0.750 inches

Center To Center Distance Between Bolt Holes Along Width:

0.891 inches

Center To Center Distance Between Bolt Holes Along Length:

1.875 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.344 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.578 inches

Bolt Hole Quantity:

4

Flange Length:

2.562 inches

Flange Width:

2.047 inches

Bolt Hole Diameter:

0.406 inches

Flange Section Style:

Plain recessed face

Face Seating Surface Condition:

Ground

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch fuel/oil, hydrocarbon

Special Features:

Split flange type

Material:

Steel

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, class 3, type 2 federal specification 1st treatment response or qq-z-325, type 2, class 2 federal specification 2nd treatment response

Style Designator:

Rectangular, with bolt holes

Specification Data:

81349-mil-f-52525c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23300