

View Online at <https://aerobasegroup.com/nsn/4730-01-083-4432>

**Furnished Items:**

Screw and lock washer and packing, preformed

**Recess Diameter:**

1.531 inches

**Recess Depth:**

0.245 inches

**Thickness:**

0.562 inches

**Pipe Size For Which Designed:**

0.750 inches

**Center To Center Distance Between Bolt Holes Along Width:**

0.891 inches

**Center To Center Distance Between Bolt Holes Along Length:**

1.875 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.344 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.578 inches

**Bolt Hole Quantity:**

4

**Flange Length:**

2.562 inches

**Flange Width:**

2.047 inches

**Bolt Hole Diameter:**

0.406 inches

**Flange Section Style:**

Plain recessed face

**Face Seating Surface Condition:**

Ground

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch fuel/oil, hydrocarbon

**Special Features:**

Split flange type

**Material:**

Steel

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, class 3, type 2 federal specification 1st treatment response or qq-z-325, type 2, class 2 federal specification 2nd treatment response

**Style Designator:**

Rectangular, with bolt holes

**Specification Data:**

81349-mil-f-52525c government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23300