

View Online at <https://aerobasegroup.com/nsn/4730-01-083-5852>

Thread Class:

2a center bulkhead

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flareless (tube) all ends

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

12 center bulkhead

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.312 inches center bulkhead

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

1.000 inches all ends

Nominallength:

2.719 inches

Material:

Steel comp 303 or steel comp 304 or steel comp 316

Material Specification:

Fed standard 66 federal standard all material responses

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Flaremess w/ bulkhead threads

Thread Series Designator:

Un center bulkhead

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 bulkhead nut

Specification Data:

96906-ms51812 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

20a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.