

View Online at <https://aerobasegroup.com/nsn/4730-01-083-5852>

**Thread Class:**

2a center bulkhead

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

Flareless (tube) all ends

**Connection Type:**

Threaded external tube all ends

**Thready Qty Per Inch (tpi):**

12 center bulkhead

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.312 inches center bulkhead

**Seat Angle:**

12.0 degrees all ends

**Outside Diameter Tube Accommodated:**

1.000 inches all ends

**Nominallength:**

2.719 inches

**Material:**

Steel comp 303 or steel comp 304 or steel comp 316

**Material Specification:**

Fed standard 66 federal standard all material responses

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Flaremess w/ bulkhead threads

**Thread Series Designator:**

Un center bulkhead

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve and 1 bulkhead nut

**Specification Data:**

96906-ms51812 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

20a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.