

View Online at <https://aerobasegroup.com/nsn/4730-01-085-1329>

Body Style:

Plain

Concentric Hole Depth:

0.968 inches

Concentric Hole Diameter:

0.234 inches

Overall Length:

1.437 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

0.750 inches

First End Thread Length:

0.300 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.498 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.875 inches

First Radial Fluid Hole Diameter:

0.219 inches

Distance From First Radial Hole Center To End Of Bolt:

0.812 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.250 inches

Wrenching Feature Height:

0.172 inches

Pressure Rating:

3000.000 pounds per square inch

First End Thread Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unf

First End Seat Angle:

45.0 degrees

First End Thread Size:

0.500 inches

Special Features:

Bolt head drilled for lockwire

Material:

Aluminum

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Specification Data:

80205-nas551 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-a-8625 spec.