

View Online at <https://aerobasegroup.com/nsn/4730-01-091-8033>

Thread Class:

2a all ends

Connection Style:

Flared (tube) all ends

Connection Type:

Threaded external tube all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

37.0 degrees all ends

Outside Diameter Tube Accommodated:

0.250 inches all ends

Nominallength:

2.047 inches

Special Features:

Two through holes, 0.061 in. Min 0.066 in. Maximum dia, located 0.450 in. From bulkhead end

Material:

Aluminum alloy

Material Specification:

Qq-a-225/4, alloy 2014, t6 federal specification single material response or qq-a-225/6, alloy 2024, t6 or t851 federal specification single material response or qq-a-225/9, alloy 7075, t73 federal specification single material response or qq-a-367, alloy 2014, t6 federal specification single material response or qq-a-367, alloy 7075, t73 federal specification single material response

Media For Which Designed:

Fluid single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Style Designator:

Flared w/ bulkhead thread

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.