

View Online at <https://aerobasegroup.com/nsn/4730-01-095-7032>

**Thread Class:**

2a first quick disconnect end

**Unable To Decode:**

Unable to decode and unable to decode and unable to decode

**Second End Flange Shape Style (non-core):**

Err-090

**First Leg Length:**

0.350 inches

**Second Leg Length:**

2.310 inches

**Bolt Hole Quantity:**

4

**Maximum Operating Temp:**

160.0 degrees fahrenheit single response

**Connection Style:**

Recessed second quick disconnect end

**Connection Type:**

Threaded external boss first quick disconnect end

**Features Provided:**

Safety locking feature

**Thready Qty Per Inch (tpi):**

16 first quick disconnect end

**Second End Relationship With First End:**

Not identical

**Maximum Operating Pressure:**

60.0 pounds per square inch single response

**Thread Size:**

1.313 inches first quick disconnect end

**Flow Angle:**

90.0 degrees

**Bolt Hole Diameter:**

0.210 inches

**Special Features:**

Furnished items include; preformed packing, spring and pin.

**Material:**

Aluminum alloy 2024 body

**Material Specification:**

Qq-a-225/6, t351 federal specification single material response body

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize body

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response body

**Style Designator:**

Coupling assembly

**Thread Series Designator:**

Un first quick disconnect end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531u0

**Mil-std (military Standard):**

Mil-a-8625 spec.