NSN 4730-01-095-7032

Self-sealing Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-095-7032

Thread Class: 2a first quick disconnect end **Unable To Decode:** Unable to decode and unable to decode and unable to decode Second End Flange Shape Style (non-core): Err-090 First Leg Length: 0.350 inches Second Leg Length: 2.310 inches **Bolt Hole Quantity: Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Recessed second quick disconnect end **Connection Type:** Threaded external boss first quick disconnect end **Features Provided:** Safety locking feature Thready Qty Per Inch (tpi): 16 first quick disconnect end Second End Relationship With First End: Not identical **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 1.313 inches first quick disconnect end Flow Angle: 90.0 degrees **Bolt Hole Diameter:** 0.210 inches **Special Features:** Furnished items include; preformed packing, spring and pin. Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6, t351 federal specification single material response body Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize body

NSN 4730-01-095-7032

Self-sealing Coupling Assembly - Page 2 of 2



Surface Treatment Specification:

Mil-a-8625 military specification single treatment response body

Style Designator:

Coupling assembly

Thread Series Designator:

Un first quick disconnect end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A531u0

Mil-std (military Standard):

Mil-a-8625 spec.