

View Online at <https://aerobasegroup.com/nsn/4730-01-096-9128>

Thread Class:

2a 1st end

End Application:

Support equipment, mx peacekeeper missile; tractor, aircraft towing mb-4; trailer, semi m870; truck, fire p-22; trailer, semi, transporter 22 1/2 ton; crane, wheel mounted, 7 1/2 ton rt48mc; power unit, front 12 1/2 ton 4x4, mk48 mod dlvs; trailer, semi, 65-t, 16whl, c0879, m793; scaper, elv non-sectionalized, 613bsns; trailer, semi, low bed 40 ton, 12 whl m870; nsn 4210-01-486-1035 tfft (tactical fire fighting truck); 2320-01-097-0248, 2320-01-097-0249, 2320-01-100-7672, 2320-01-097-0260, 2320-01-195-7641 hemtt (heavy expanded mobility trucks); mrap cougar iss

Connection Style:

Plain (pipe) 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

0.531 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Tubing Wall Thickness For Which Designed:

0.032 inches 1st end

Nominallength:

1.234 inches

Material:

Copper alloy

Media For Which Designed:

Air single response

Thread Series Designator:

Uns 1st end

Furnished Items And Quantity:

1 tube coupling nut w/sleeve

Specification Data:

81343-j246 professional/industrial association standard

Specification Or Standard:

6a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: