

View Online at <https://aerobasegroup.com/nsn/4730-01-112-1278>

**Thread Class:**

3a 2nd end bulkhead

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**Connection Style:**

Swaged w/ grooves (tube) 1st end

**Leg Length:**

1.688 inches 2nd end

**Connection Type:**

Unthreaded internal tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.562 inches 2nd end bulkhead

**Seat Angle:**

12.0 degrees 2nd end

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.375 inches all ends

**Tubing Wall Thickness For Which Designed:**

0.250 inches 1st end

**Special Features:**

Fitting shall be polytetrafluoroethylene coated on interal surface only to a distance of 0.220 min 0.270 maximum in. Deep

**Material:**

Steel comp xm-10

**Material Specification:**

Ams5656 assn standard single material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Passivate outside

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response outside

**Thread Series Designator:**

Unjf 2nd end bulkhead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-s-5002 spec.