

View Online at <https://aerobasegroup.com/nsn/4730-01-117-0758>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

X2m assault amphibious vehicle, command (aavc-7a1)

**Connection Style:**

Flared (tube) 1st end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches all ends

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Nominallength:**

1.700 inches

**Material:**

Stainless steel

**Material Specification:**

66, 300 series federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 1 or 2 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve and 1 preformed packing

**Specification Data:**

96906-ms51525 government standard and 81343-j-514 professional/industrial association standard

**Specification Or Standard:**

6b figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.