

View Online at <https://aerobasegroup.com/nsn/4730-01-125-6381>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

X2m assault amphibious vehicle, command (aavc-7a1)

Connection Style:

Flared (tube) 1st end

Leg Length:

1.516 inches 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches all ends

Seat Angle:

37.0 degrees 1st end

Flow Angle:

45.0 degrees

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Material:

Stainless steel

Material Specification:

66, 300 series federal standard single material response

Media For Which Designed:

Hydraulic fluid 2nd response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 1 or 2 federal specification single treatment response

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

1 tube coupling nut w/sleeve and 1 preformed packing

Specification Data:

96906-ms51528 government standard and 81349-mil-f-1866 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.