

View Online at <https://aerobasegroup.com/nsn/4730-01-126-5998>

**Body Style:**

Relieved

**Concentric Hole Depth:**

0.820 inches

**Concentric Hole Diameter:**

0.125 inches

**Overall Length:**

Between 1.141 inches and 1.173 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Flared

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Width Across Flats:**

0.580 inches

**First End Thread Length:**

0.531 inches

**Wrenching Feature Style:**

Hexagon

**First Diameter From Wrenching Feature:**

Between 0.309 inches and 0.312 inches

**Second Diameter From Wrenching Feature:**

0.312 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.090 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

0.340 inches

**First Radial Fluid Hole Diameter:**

0.125 inches

**Distance From First Radial Hole Center To End Of Bolt:**

0.754 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

0.969 inches

**Wrenching Feature Height:**

Between 0.172 inches and 0.201 inches

**First End Thread Series Designator:**

Unf

**First End Seat Angle:**

45.0 degrees

**First End Thread Size:**

0.312 inches

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0

**Mil-std (military Standard):**

Mil-s-18732 spec.