

View Online at <https://aerobasegroup.com/nsn/4730-01-141-4131>

Thread Class:

2a center bulkhead

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

Buf engine, aircraft, f100-pw-200 (f-16a/.B/c/d)

Connection Style:

Flared w/ gasket seal (boss) 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.312 inches all ends

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.125 inches 1st end

Nominallength:

1.870 inches

Material:

Stainless steel

Material Specification:

66, 300 series federal specification single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response

Thread Series Designator:

Unf center bulkhead

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut

Specification Data:

96906-ms51520 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0