NSN 4730-01-143-1432

Swivel Retaining Pipe Flange - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-143-1432
Recess Diameter:
Between 2.521 inches and 2.541 inches
Recess Depth:
Between 0.470 inches and 0.480 inches
Thickness:
1.190 inches
Pipe Size For Which Designed:
1.500 inches
Center To Center Distance Between Bolt Holes Along Width:
1.360 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 3.125 inches and 3.135 inches
Outside Edge To Bolt Hole Center Distance Along Width:
Between 0.627 inches and 0.687 inches
Outside Edge To Bolt Hole Center Distance Along Length:
0.680 inches
Bolt Hole Quantity:
4
Flange Length:
Between 4.380 inches and 4.500 inches
Flange Width:
3.660 inches
Bolt Hole Diameter:
0.656 inches
Neck Height:
0.500 inches
Flange Section Style:
Recessed face, raised neck
Face Seating Surface Condition:
Ground
Maximum Operating Pressure And Media For Which Designed:
6000.0 pounds per square inch any acceptable
Special Features:
Split flange
Material:
Iron
Style Designator:
Rectangular, with bolt holes
Specification Data:

81343-j518 professional/industrial association standard

Specification Or Standard:

4 figure and 62 code

NSN 4730-01-143-1432

Swivel Retaining Pipe Flange - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300