

View Online at <https://aerobasegroup.com/nsn/4730-01-156-4845>

**Furnished Items:**

Screw

**Thickness:**

1.594 inches

**Socket Depth:**

0.750 inches

**Socket Diameter:**

2.387 inches

**Pipe Size For Which Designed:**

2.000 inches

**Center To Center Distance Between Bolt Holes Along Width:**

3.062 inches

**Center To Center Distance Between Bolt Holes Along Length:**

3.062 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.594 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.594 inches

**Bolt Hole Quantity:**

4

**Flange Length:**

4.250 inches

**Flange Width:**

4.250 inches

**Bolt Hole Diameter:**

0.656 inches

**Raised Face Height:**

0.126 inches

**Raised Face Diameter:**

2.373 inches

**Neck Height:**

0.840 inches

**Flange Section Style:**

Raised face, socket neck

**Face Seating Surface Condition:**

Ground

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch any acceptable

**Special Features:**

With one aluminum alloy sleeve, one o-ring, synthetic rubber and four nickel-copper alloy washers

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-763, cond a federal specification single material response

**Style Designator:**

Rectangular, with bolt holes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23300