

View Online at <https://aerobasegroup.com/nsn/4730-01-161-1247>

Concentric Hole Depth:

Between 2.250 inches and 2.310 inches

Concentric Hole Diameter:

Between 0.168 inches and 0.175 inches

Overall Length:

Between 2.411 inches and 2.494 inches

Width Across Flats:

Between 0.739 inches and 0.753 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.492 inches and 0.500 inches

Second Diameter From Wrenching Feature:

Between 0.418 inches and 0.420 inches

Third Diameter From Wrenching Feature:

Between 0.308 inches and 0.310 inches

Fourth Diameter From Wrenching Feature:

Between 0.418 inches and 0.420 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 0.347 inches and 0.352 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 1.003 inches and 1.023 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

Between 1.107 inches and 1.117 inches

First Radial Fluid Hole Diameter:

Between 0.160 inches and 0.180 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.370 inches and 0.375 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.636 inches and 1.669 inches

Wrenching Feature Height:

Between 0.240 inches and 0.260 inches

Material:

Steel comp 316 or steel comp 347

Material Specification:

Qq-s-763 cond a federal specification all material responses

Surface Treatment:

Passivate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0