## NSN 4730-01-166-3160

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-166-3160

Body Style:
Plain
Head Diameter:
1.312 inches
Distance From Centerline To Flat:
0.563 inches
Concentric Hole Depth:
0.375 inches
Concentric Hole Diameter:
0.250 inches
Overall Length:
3.500 inches
First End Connection Type:
Threaded internal tube
First End Style Designator:
High pressure flare
First End Thread Class:
3b
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded external tube
Second End Thread Class:
3a
Second End Thread Direction:
Right-hand
First End Thread Length:
0.109 inches
Second End Thread Length:
0.700 inches
Wrenching Feature Style:
Round with wrench flats
First Diameter From Wrenching Feature:
0.970 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
2.365 inches
First Radial Fluid Hole Diameter:
0.093 inches
Second Radial Fluid Hole Diameter:
0.093 inches
Distance From First Radial Hole Center To End Of Bolt:
2.725 inches

## **NSN 4730-01-166-3160** Fluid Passage Bolt - Page 2 of 2



Distance From Second Radial Hole Center To End Of Bolt:
1.450 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
3.300 inches
Wrenching Feature Height:
0.200 inches
First End Thread Series Designator:
Jnjf
First End Seat Angle:
60.0 degrees
First End Thread Size:
0.250 inches
Second End Seat Angle:
60.0 degrees
Second End Thread Size:
0.750 inches
Second End Thread Series Designator:
Jnjf
Material:
Stainless steel
Material Specification:
Mil-s-8844, class 3 military specification single material response
Surface Treatment:
Cadmium and chromium
Surface Treatment Specification:
Ps131 mfr ref 1st treatment response and ps101-7 mfr ref 1st treatment response or ps923 mfr ref 1st treatment response
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A121a0
Mil-std (military Standard):
Mil-s-8844 spec.