## NSN 4730-01-174-1199

Pipe To Tube Union - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-174-1199

Pipe Size Accommodated:  1.000 inches 2nd end  Thread Class:  2a 1st end  Seat Type:  Ball-cone  Reducer Type:  Concentric  Connection Style:  Socket (pipe) 2nd end  Connection Type:  Unthreaded internal pipe 2nd end  Thready Qty Per Inch (tpi):  12 1st end  Maximum Operating Pressure:  3000.0 pounds per square inch single response  Thread Size:  1.062 inches 1st end  Coupling Flange Shape:  Round  Outside Diameter Tube Accommodated:  0.750 inches 1st end
Thread Class:  2a 1st end  Seat Type:  Ball-cone  Reducer Type:  Concentric  Connection Style:  Socket (pipe) 2nd end  Connection Type:  Unthreaded internal pipe 2nd end  Thready Qty Per Inch (tpi):  12 1st end  Maximum Operating Pressure:  3000.0 pounds per square inch single response  Thread Size:  1.062 inches 1st end  Coupling Flange Shape:  Round  Outside Diameter Tube Accommodated:
2a 1st end Seat Type: Ball-cone Reducer Type: Concentric Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Seat Type: Ball-cone Reducer Type: Concentric Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Reducer Type: Concentric Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Reducer Type: Concentric Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Connection Style: Socket (pipe) 2nd end Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Socket (pipe) 2nd end  Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end  Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end  Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Connection Type: Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Unthreaded internal pipe 2nd end Thready Qty Per Inch (tpi): 12 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Thready Qty Per Inch (tpi):  12 1st end  Maximum Operating Pressure:  3000.0 pounds per square inch single response  Thread Size:  1.062 inches 1st end  Coupling Flange Shape:  Round  Outside Diameter Tube Accommodated:
12 1st end  Maximum Operating Pressure: 3000.0 pounds per square inch single response  Thread Size: 1.062 inches 1st end  Coupling Flange Shape: Round  Outside Diameter Tube Accommodated:
Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
3000.0 pounds per square inch single response  Thread Size: 1.062 inches 1st end  Coupling Flange Shape: Round  Outside Diameter Tube Accommodated:
Thread Size: 1.062 inches 1st end Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
1.062 inches 1st end  Coupling Flange Shape:  Round  Outside Diameter Tube Accommodated:
Coupling Flange Shape: Round Outside Diameter Tube Accommodated:
Round Outside Diameter Tube Accommodated:
Outside Diameter Tube Accommodated:
0.750 inches 1st end
Nominallength:
6.560 inches
Special Features:
Second end has boss feature
Material:
Stainless steel thread piece
Material Specification:
Qq-s-763, cl 304, cond a federal specification 1st material response thread piece
Style Designator:
Screwed
Thread Series Designator:
Un 1st end
Furnished Items And Quantity:
1 short coupling nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4730-01-174-1199

Pipe To Tube Union - Page 2 of 2



Fiig:

A080b0