NSN 4730-01-216-1088

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-216-1088 Second End Style Designator (non-core): Err-090 **Quick Disconnect Method:** Push-pull all ends **Second Fluid End Connection Type:** Threaded external pipe **Connection Style:** Plain first fluid end connection **Connection Type:** Threaded internal pipe first fluid end connection Second End Relationship With First End: Not identical **Maximum Operating Pressure And Media For Which Designed:** 150.0 pounds per square inch air **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 0.250 inches first fluid end connection Second End Thread Size: 0.250 inches **Second End Thread Series Designator:** Npt Material: Steel **Surface Treatment:** Cadmium Style Designator: Coupling assembly **Thread Series Designator:** Npt first fluid end connection **Specification Data:** 58536-a-a-59439 professional/industrial association specification **Specification Or Standard:** 1 type and 2 type and 1 style and 2 style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A531s0

NSN 4730-01-216-1088

Quick Disconnect Coupling Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-c-4109 spec.