NSN 4730-01-222-1720

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-01-222-1720

| Body Style:PlainConcentric Hole Depth:1.312 inchesConcentric Hole Diameter:0.296 inchesOverall Length:1.562 inchesFirst End Connection Type:Threaded external tubeFirst End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inchesFirst End Thread Length: |
|--|
| Concentric Hole Depth:1.312 inchesConcentric Hole Diameter:0.296 inchesOverall Length:1.562 inchesFirst End Connection Type:Threaded external tubeFirst End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inches |
| 1.312 inches Concentric Hole Diameter: 0.296 inches Overall Length: 1.562 inches First End Connection Type: Threaded external tube First End Style Designator: Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| Concentric Hole Diameter:0.296 inchesOverall Length:1.562 inchesFirst End Connection Type:Threaded external tubeFirst End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inches |
| 0.296 inches Overall Length: 1.562 inches First End Connection Type: First End Connection Type: Threaded external tube First End Style Designator: Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| Overall Length:1.562 inchesFirst End Connection Type:Threaded external tubeThreaded external tubeFirst End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inches |
| 1.562 inches First End Connection Type: Threaded external tube First End Style Designator: Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| First End Connection Type:Threaded external tubeFirst End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inches |
| Threaded external tube First End Style Designator: Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| First End Style Designator:FlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:0.813 inches |
| Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| 3a First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| First End Thread Direction: Right-hand Width Across Flats: 0.813 inches |
| Right-hand Width Across Flats: 0.813 inches |
| Width Across Flats: 0.813 inches |
| 0.813 inches |
| |
| First End Thread Length: |
| |
| 0.469 inches |
| Wrenching Feature Style: |
| Hexagon |
| First Diameter From Wrenching Feature: |
| 0.560 inches |
| Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: |
| Between 0.870 inches and 0.880 inches |
| First Radial Fluid Hole Diameter: |
| 0.250 inches |
| Distance From First Radial Hole Center To End Of Bolt: |
| Between 0.478 inches and 0.483 inches |
| Length From Bearing Surface Of Wrenching Feature To Bolt End: |
| 1.344 inches |
| Wrenching Feature Height: |
| 0.219 inches |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| First End Thread Series Designator: |
| Unjf |
| First End Seat Angle: |
| 45.0 degrees |
| First End Thread Size: |
| 0.562 inches |

NSN 4730-01-222-1720

Fluid Passage Bolt - Page 2 of 2

Material:

Steel comp 304

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A121a0

