NSN 4730-01-223-0536

Tube To Boss Straight Adapter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-01-223-0536 |
|---|
| Thread Class: |
| 2a center bulkhead |
| Maximum Operating Temp: |
| 400.0 degrees fahrenheit single response |
| Connection Style: |
| Flared w/ gasket seal (boss) 2nd end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 center bulkhead |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.312 inches center bulkhead |
| Seat Angle: |
| 37.0 degrees 1st end |
| Criticality Code Justification: |
| Feat |
| Outside Diameter Tube Accommodated: |
| 1.000 inches 1st end |
| Nominallength: |
| 3.140 inches |
| Special Features: |
| Weapon system essential |
| Material: |
| Steel |
| Surface Treatment Specification: |
| J514 assn standard single treatment response |
| Thread Series Designator: |
| Un center bulkhead |
| Furnished Items And Quantity: |
| 2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut |
| Specification Data: |
| 81349 - mil-f-18866 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

. -

A080b0

NSN 4730-01-223-0536

Tube To Boss Straight Adapter - Page 2 of 2



Mil-std (military Standard):

Mil-f-18866 spec.