

View Online at <https://aerobasegroup.com/nsn/4730-01-238-6442>

Thread Class:

2a 1st end

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

Wva 10kw gohz tqg generator

Connection Style:

Plain (pipe) 2nd end

Leg Length:

0.860 inches 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

45.0 degrees

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Steel comp 1010 or steel comp 12l14

Material Specification:

Astm a576 national specification all material responses or 66 federal standard all material responses

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Zinc

Surface Treatment Specification:

J514 assn standard single treatment response and mil-c-81562, type 2, cl 3 military specification 1st treatment response and astm b633, type 2, cl sc1 assn standard 2nd treatment response

Thread Series Designator:

Unf 1st end

Specification Data:

96906 - ms51508 government standard and 81349 - mil-f-18866 government standard

Specification Or Standard:

4e figure and 4-4 designator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-c-81562 spec.